



# STOCK SILO

## DESIGN AND FUNCTION

Stock Silos are used for interim storage of sophisticated and high-quality bulk solids, such as pellets, food and feed, raw material or powder. We offer standard silo diameters up to 2,850 mm, but we will gladly add additional diameters for our customers.



<b>Products.</b>	For example: plastics, food and feed, raw materials, pellets, agglomerates, powders, grains, cereals, flakes, cut / ground freight.
<b>Feeding.</b>	Tangential feeding via pressure transport.
<b>Manhole.</b>	Manhole with end switches for better maintenance of the silo.
<b>Volume.</b>	Volumes from 3 m <sup>3</sup> to 40 m <sup>3</sup> .
<b>Materials.</b>	Aluminum, standard or stainless steel.
<b>Railing/vertical ladder.</b>	Optional with guard rails on top and vertical ladder, including back protection.
<b>Options.</b>	Other options and sizes available on request.



## STOCK SILO TECHNICAL DETAILS

Volume [m³]	Cylinder Ø [mm]	Cylinder height [mm]	Total height [mm]
3	1.750	1.500	2.600
5	1.750	2.500	3.600
8	2.200	2.500	3.600
10	2.200	3.000	4.100
15	2.500	3.500	4.660
20	2.500	4.500	5.660
25	2.500	5.500	6.660
30	2.850	5.000	6.160
40	2.850	6.500	7.660